

Product Lineup

Material: Fluoropolymer
 Recommended Temperature: 200°C / 392° F

NFPR Standard 1.8:1 Shrink Ratio Standard Length: 1700 mm Color: Translucent MOQ/SPQ:100/100 [pcs]

Parts No.	Metric			Imperial			French
	Expanded I.D. Min.	Full Recovered I.D. Max.	Full Recovered Wall Thickness	Expanded I.D. Min.	Full Recovered I.D. Max.	Full Recovered Wall Thickness	Suitable for
NFPR006	0.72 mm	0.40 mm	0.25 +/- 0.05 mm	0.0283"	0.0157"	0.0098 +/- 0.0020"	1.3 -2.1 Fr
NFPR011	1.44 mm	0.80 mm	0.25 +/- 0.05 mm	0.0567"	0.0315"	0.0098 +/- 0.0020"	2.5 - 4.3 Fr
NFPR018	2.34 mm	1.30 mm	0.25 +/- 0.05 mm	0.0921"	0.0512"	0.0098 +/- 0.0020"	4.0 - 7.0 Fr
NFPR029	3.78 mm	2.10 mm	0.30 +/- 0.05 mm	0.1488"	0.0827"	0.0118 +/- 0.0020"	6.4 - 11.3 Fr

NFPM Ultra Small 1.6:1 Shrink Ratio Standard Length: 1000 mm Color: Translucent MOQ/SPQ:100/100 [pcs]

Parts No.	Metric			Imperial			French
	Expanded I.D. Min.	Full Recovered I.D. Max.	Full Recovered Wall Thickness	Expanded I.D. Min.	Full Recovered I.D. Max.	Full Recovered Wall Thickness	Suitable for
NFPM0030	0.38 mm	0.23 mm	0.20 +/- 0.05 mm	0.0150"	0.0091"	0.0079 +/- 0.0020"	1.0 Fr
NFPM0037	0.46 mm	0.28 mm	0.20 +/- 0.05 mm	0.0181"	0.0110"	0.0079 +/- 0.0020"	1.2 Fr
NFPM0042	0.51 mm	0.33 mm	0.20 +/- 0.05 mm	0.0201"	0.0130"	0.0079 +/- 0.0020"	1.4 Fr

NFPS Standard 1.6:1 Shrink Ratio Standard Length: 1700 mm Color: Translucent MOQ/SPQ:100/100 [pcs]

Parts No.	Metric			Imperial			French
	Expanded I.D. Min.	Full Recovered I.D. Max.	Full Recovered Wall Thickness	Expanded I.D. Min.	Full Recovered I.D. Max.	Full Recovered Wall Thickness	Suitable for
NFPS005	0.64 mm	0.40 mm	0.20 +/- 0.05 mm	0.0252"	0.0157"	0.0079 +/- 0.0020"	1.5 Fr
NFPS007	0.80 mm	0.50 mm	0.20 +/- 0.05 mm	0.0315"	0.0197"	0.0079 +/- 0.0020"	2.0 Fr
NFPS008	0.96 mm	0.60 mm	0.20 +/- 0.05 mm	0.0378"	0.0236"	0.0079 +/- 0.0020"	2.5 Fr
NFPS009	1.12 mm	0.70 mm	0.20 +/- 0.05 mm	0.0441"	0.0276"	0.0079 +/- 0.0020"	3.0 Fr
NFPS010	1.28 mm	0.80 mm	0.20 +/- 0.05 mm	0.0504"	0.0315"	0.0079 +/- 0.0020"	3.5 Fr
NFPS012	1.44 mm	0.90 mm	0.20 +/- 0.05 mm	0.0567"	0.0354"	0.0079 +/- 0.0020"	4.0 Fr
NFPS013	1.60 mm	1.00 mm	0.20 +/- 0.05 mm	0.0630"	0.0394"	0.0079 +/- 0.0020"	4.5 Fr
NFPS017	2.08 mm	1.30 mm	0.20 +/- 0.05 mm	0.0819"	0.0512"	0.0079 +/- 0.0020"	5.0 Fr
NFPS021	2.56 mm	1.60 mm	0.275 +/- 0.05 mm	0.1008"	0.0630"	0.0108 +/- 0.0020"	6 - 8 Fr
NFPS028	3.36 mm	2.10 mm	0.275 +/- 0.05 mm	0.1323"	0.0827"	0.0108 +/- 0.0020"	8 - 11 Fr

NFPS Large 1.6~1.4:1 Shrink Ratio Standard Length: 1000 mm Color: Translucent MOQ/SPQ:50/50 [pcs]

Parts No.	Metric			Imperial			French
	Expanded I.D. Min.	Full Recovered I.D. Max.	Full Recovered Wall Thickness	Expanded I.D. Min.	Full Recovered I.D. Max.	Full Recovered Wall Thickness	Suitable for
NFPS036	4.45 mm	2.79 mm	0.275 +/- 0.05 mm	0.1752"	0.1098"	0.0108 +/- 0.0020"	11 - 12 Fr
NFPS038	4.78 mm	2.92 mm	0.275 +/- 0.05 mm	0.1882"	0.1150"	0.0108 +/- 0.0020"	13 - 15 Fr
NFPS052	6.05 mm	4.32 mm	0.275 +/- 0.05 mm	0.2382"	0.1701"	0.0108 +/- 0.0020"	15 - 17 Fr

NFP Extra Large 1.5:1 Shrink Ratio Standard Length: 1500 mm Color: Translucent MOQ/SPQ:25/25 [pcs]

Parts No.	Metric			Imperial			French
	Expanded I.D. Min.	Full Recovered I.D. Max.	Full Recovered Wall Thickness	Expanded I.D. Min.	Full Recovered I.D. Max.	Full Recovered Wall Thickness	Suitable for
NFP064	7.62 mm	5.08 mm	0.33 +/- 0.05 mm	0.3000"	0.2000"	0.0130 +/- 0.0020"	16 - 22 Fr
NFP074	8.89 mm	5.93 mm	0.33 +/- 0.05 mm	0.3500"	0.2335"	0.0130 +/- 0.0020"	18 - 26 Fr
NFP085	10.16 mm	6.77 mm	0.33 +/- 0.05 mm	0.4000"	0.2665"	0.0130 +/- 0.0020"	21 - 30 Fr
NFP095	11.43 mm	7.62 mm	0.33 +/- 0.05 mm	0.4500"	0.3000"	0.0130 +/- 0.0020"	23 - 34 Fr

NFP Standard 1.4:1 Shrink Ratio Standard Length: 1500 mm Color: Translucent MOQ/SPQ:100/100 [pcs]

Parts No.	Metric			Imperial			French
	Expanded I.D. Min.	Full Recovered I.D. Max.	Full Recovered Wall Thickness	Expanded I.D. Min.	Full Recovered I.D. Max.	Full Recovered Wall Thickness	Suitable for
NFP006	0.71 mm	0.50 mm	0.20 +/- 0.05 mm	0.0280"	0.0197"	0.0079 +/- 0.0020"	1.8 Fr
NFP007	0.86 mm	0.60 mm	0.20 +/- 0.05 mm	0.0339"	0.0236"	0.0079 +/- 0.0020"	2.2 Fr
NFP008	1.00 mm	0.70 mm	0.20 +/- 0.05 mm	0.0394"	0.0276"	0.0079 +/- 0.0020"	2.5 Fr
NFP010	1.14 mm	0.80 mm	0.20 +/- 0.05 mm	0.0449"	0.0315"	0.0079 +/- 0.0020"	3.0 Fr
NFP011	1.29 mm	0.90 mm	0.20 +/- 0.05 mm	0.0508"	0.0354"	0.0079 +/- 0.0020"	3.5 Fr
NFP013	1.57 mm	1.10 mm	0.20 +/- 0.05 mm	0.0618"	0.0433"	0.0079 +/- 0.0020"	4.0 Fr
NFP017	2.00 mm	1.40 mm	0.20 +/- 0.05 mm	0.0787"	0.0511"	0.0079 +/- 0.0020"	5.0 Fr
NFP021	2.30 mm	1.70 mm	0.25 +/- 0.05 mm	0.0906"	0.0669"	0.0098 +/- 0.0020"	6.0 Fr
NFP026	2.84 mm	2.10 mm	0.25 +/- 0.05 mm	0.1118"	0.0827"	0.0098 +/- 0.0020"	7 - 9 Fr
NFP030	3.38 mm	2.50 mm	0.25 +/- 0.05 mm	0.1331"	0.0984"	0.0098 +/- 0.0020"	8 - 11 Fr

*Junkosha is manufactured and inspected in mm and values in inch are for reference only.

**Peelable Heat Shrink Tubing meets the requirement of USP Plastic Class VI. Certificates available on request.